



TruStream Sampling Assembly Specifications

250 milliliter - PN 111450



Component / Parameter	Specification / Material
Physical	
Capacity	250 ml
Bag Size (L x W)	8" x 5" / 203.2mm x 127mm
Fill Tubing Length	36" / 914.4mm
Needle	18Ga x 1.5" / 1.2mm x 38.1mm
Condition	Sterile (Fluid Path)
Materials	
Bag Film	PVC (14 mil)
Fill Tubing	PVC
Fittings	PP / Acrylic
Needle	PP / 304SS
Technical (Bag Film)	
Tensile Strength, ASTM D882 (psi)	2400 min (MD)
Elongation, ASTM D882 (%)	305 min (MD)
Modulus, ASTM D882 (psi)	1000 min (MD)
Oxygen Permeable	Yes
Regulatory	
USP Class VI / ISO 10993 Compliant	Yes
TSE / BSE Compliant	Yes
BPA Free	Yes
Latex Free	Yes
DEHP Free	No

*DEHP Free defined as DEHP Content < 0.1% w/w

Component Packaging	Configuration	Length	Width	Height	Shipping Weight
TruStream	100 per case/individually packaged	16" / 406.4mm	11" / 279.4mm	12" / 304.8mm	9 lbs. / 4.1 kg



TruStream Sampling Assembly Specifications

2 Liter - PN 111730



Component / Parameter	Specification / Material
Physical	
Capacity	2 L
Bag Size (L x W)	14" x 7" / 355.6 x 177.8mm
Fill Tubing Length	36" / 914.4mm
Needle	18Ga x 1.5" / 1.2mm x 38.1mm
Condition	Sterile (Fluid Path)
Materials	
Bag Film	PVC (14 mil)
Fill Tubing	PVC
Fittings	PP / Acrylic
Needle	PP / 304SS
Technical (Bag Film)	
Tensile Strength, ASTM D882 (psi)	2400 min (MD)
Elongation, ASTM D882 (%)	305 min (MD)
Modulus, ASTM D882 (psi)	1000 min (MD)
Oxygen Permeable	Yes
Regulatory	
USP Class VI / ISO 10993 Compliant	Yes
TSE / BSE Compliant	Yes
BPA Free	Yes
Latex Free	Yes
DEHP Free	No

*DEHP Free defined as DEHP Content < 0.1% w/w

Component Packaging	Configuration	Length	Width	Height	Shipping Weight
TruStream	100 per case/individually packaged	20" / 508mm	12" / 304.8mm	9" / 228.6mm	17 lbs. / 7.7 kg



TruStream Sampling Assembly Specifications

7 Liter - PN 111930



Component / Parameter	Specification / Material
Physical	
Capacity	7 L
Bag Size (L x W)	17" x 12" / 431.8 x 304.8mm
Fill Tubing Length	36" / 914.4mm
Needle	18Ga x 1.5" / 1.2 mm x 38.1mm
Condition	Sterile (Fluid Path)
Materials	
Bag Film	PVC (14 mil)
Fill Tubing	PVC
Fittings	PP / Acrylic
Needle	PP / 304SS
Technical (Bag Film)	
Tensile Strength, ASTM D882 (psi)	2400 min (MD)
Elongation, ASTM D882 (%)	305 min (MD)
Modulus, ASTM D882 (psi)	1000 min (MD)
Oxygen Permeable	Yes
Regulatory	
USP Class VI / ISO 10993 Compliant	Yes
TSE / BSE Compliant	Yes
BPA Free	Yes
Latex Free	Yes
DEHP Free	No

*DEHP Free defined as DEHP Content < 0.1% w/w

Component Packaging	Configuration	Length	Width	Height	Shipping Weight
TruStream	100 per case/individually packaged	23" / 584.2mm	13" / 330.2mm	11" / 279.4mm	31 lbs. / 14.1 kg